



**Product Code . JL-RE-2079**

## B.O.D. Incubator

### Description

---

B.O.D. Incubator

Double wall construction.

Inner chamber made richly anodized aluminium or highly polished stainless steel sheet.

Supplied with two/three removable perforated shelves.

Exterior made out of thick mild steel sheet duly finished in white stoving enamel/powder coated paint with mat finished colour combination.

Outer double wall door is provided with magnetic gasket and lock & key arrangement.

Inner door unbreakable acrylic transparent sheet for inspection of material in the chamber without disturbing the chamber temperature.

#### Optional:

Timer 0-24 hours day night cycle.

CO<sub>2</sub> /air mixer nozzle is provided.

Internal illumination with 3 fluorescent tubes.

Microprocessor PID digital temp. Indicator-cum-controller.

Automatic Voltage stabilizer 3-5 KVA (recommended-must).

**B.O.D. Incubator Manufacturer, B.O.D. Incubator Suppliers, B.O.D. Incubator India, B.O.D. Incubator Exporter, buy B.O.D. Incubator, B.O.D. Incubator, Analytical Research Equipments, buy B.O.D. Incubator Online India**

**Inner Chamber size in mm WxDxH**

**Capacity in Cu.ft**

**Capacity**

405x405x405	2.4 cu.ft.	65 ltrs.
455x410x610	4 cu.ft.	112 ltrs.
505x415x830	6.1 cu.ft.	171 ltrs.
565x565x865	10 cu.ft.	280 ltrs.
650x580x900	12 cu.ft.	336 ltrs.
700x650x900	15 cu.ft.	420 ltrs.
{ "@context": "http://schema.org/", "@type": "Product", "name": "B.O.D. Incubator", "image": "https://www.jlabexport.com/images/catalog/product/965698053_2017-10-25.jpg", "description": "Double wall construction. Inner chamber made richly anodized aluminium or highly polished stainless steel sheet. Supplied with two/three removable perforated shelves. Exterior made out of thick mild steel sheet duly finished in white stoving enamel/powder coated paint with mat finished colour combination. Outer double wall door is provided with magnetic gasket and lock & key arrangement. Inner door unbreakable acrylic transparent sheet for inspection of material in the chamber without disturbing the chamber temperature. Optional: Timer 0-24 hours day night cycle. Co2 /air mixer nozzle is provided. Internal illumination with 3 fluorescent tubes. Microprocessor PID digital temp. Indicator-cum-controller. Automatic Voltage stabilizer 3-5 KVA (recommended-must). B.O.D. Incubator Manufacturer, B.O.D. Incubator Suppliers, B.O.D. Incubator India, B.O.D. Incubator Exporter, buy B.O.D. Incubator, B.O.D. Incubator, Analytical Research Equipments, buy B.O.D. Incubator Online India", "brand": "JLab Export", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "5" } }		