

Product Code . JL-CM-2189



Microprocessor EC-TDS-Sal Meter

Description

Microprocessor EC-TDS-Sal Meter

Features:-

16x2 Alphanumeric LCD Display

EC, TDS, Salinity & Temperature Measurements

Auto Temperature Compensation

Auto Ranging Facility

Programmable Ref. Temp & Temp. Coefficient

Microprocessor EC-TDS-Sal Meter Manufacturer India, Microprocessor EC-TDS-Sal Meter Exporters, Pharmaceutical Instruments Microprocessor EC-TDS-Sal Meter, Buy Microprocessor EC-TDS-Sal Meter, Pharmaceutical Instruments Exporters India, Pharmaceutical Instruments Suppliers, Pharmaceutical Instruments Manufacturers

90 Samples Storage Facility

Printer Attachment Facility

Microprocessor Based EC-TDS-Sal Meter model is a solid state instrument designed for precise EC, TDS,

Salinity and Temperature measurements.

The instrument uses the latest microprocessor technology and advanced engineering techniques so as to give enhanced accuracy and reproducibility.

The system has user friendly prompts, which guide you throughout the measurement process.

The instrument has 8 soft touch membrane type keys for ease of operation.

It has the storage facility for 90 samples, which are retained in the memory even when the system is switched Off.

Provision has also been made for attachment of any dot matrix printer with centronics interface so that any of the stored result can be printed.

The instrument is extremely useful for chemical & pharmaceutical industry, agriculture and soil laboratories, swimming pools, water quality control in boiler feed water, water works department, fertilizer plants, petroleum refineries, breweries, water purification plants etc.

Specifications:-

Parameter	Conductivity	TDS	Salinity	Temperature
Range Selection	Automatic	Automatic	Automatic	-
Range	0-20, 0-200uS, 0-2, 0-20, 0-200 mS	0-20, 0-200 ppm, 0-2, 0-20, 0-200 ppt	0-20, 0-200 ppm, 0-2, 0-20, 0-50 ppt	0-100oC
Accuracy	±0.5% FS ±1 Digit	±1% FS ±1 Digit	±1% of Range, ±1 Digit	0.1oC
Resolution	0.01 uS	0.01 ppm	0.01 ppm	0.1oC
Cell constant	Adjustable (0.05-10.5)	Adjustable (0.05 -10.5)	Adjustable (0.05 -10.5)	-
Temperature compensation	Auto/Manual (0-100oC)	Auto/Manual (0-50oC)	Auto/Manual	-
Temperature Coefficient	-	Adjustable (0.1-4.0%)	Adjustable (0.1-4.0%)	-
Readout	16x2 Line Alphanumeric LCD with Backlit			
Storage	Up-to 90 Samples			
Key board	8 soft touch membrane type keys			
Printer Interface	Provision for attachment of Dot-Matrix Printer with Centronics Interface			
Power	230V±10%AC,50Hz			
Dimensions (L x B x H)	Instrument: 285 x 190 x 90 mm (Approx.) Packing Box: 335 x 305 x 265 mm (Approx.)			

```
{ "@context": "http://schema.org/", "@type": "Product", "name": "Microprocessor EC-TDS-Sal Meter",  
  "image": "https://www.jlabexport.com/images/catalog/product/1188742201microprocessor-potentiometer.jpg", "description": "16x2 Alphanumeric LCD Display EC, TDS, Salinity & Temperature
```

Measurements Auto Temperature Compensation Auto Ranging Facility Programmable Ref. Temp & Temp. Coefficient Microprocessor EC-TDS-Sal Meter Manufacturer India, Microprocessor EC-TDS-Sal Meter Exporters, Pharmaceutical Instruments Microprocessor EC-TDS-Sal Meter, Buy Microprocessor EC-TDS-Sal Meter, Pharmaceutical Instruments Exporters India, Pharmaceutical Instruments Suppliers, Pharmaceutical Instruments Manufacturers 90 Samples Storage Facility Printer Attachment Facility", "brand": "JLab Export", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "5" } }
