



**Product Code . JL-RE-3892**

## Fumigation Chamber

### Description

---

Fumigation Chamber

#### **Specification:-**

Low cost, fully equipped, all purpose laboratory ovens for sample drying, baking, annealing, conditioning, sterilizing, evaporating and dehydrating and other general laboratory work.

Fully factory tested

Sturdy construction of PCGI (Powder coated Galvanized Steel)

Corrosion resistant galvanized steel interior OR of Stainless Steel.

Primary hydraulic control thermostat sets desired oven temperature. Red pilot light indicates heater operation.

Heat is transferred from the bottom up through the oven chamber by natural convection and exits through vent in the oven sides.

Synthetic door gasket made of neoprene on the double walled door.

User oriented design of shelves makes you adjust each space of shelves without difficulty.

Heating elements are placed at bottom.

Space between inner chamber and outer wall is filled with high grade mineral wool for minimal heat dissipation.

---

Door fitted with heavy duty hinges and door handle ensuring there are no leakages through the door gasket.

To work on 220/230V AV, 50/60 Hz supply.

**Fumigation Chamber Manufacturer, Fumigation Chamber Suppliers, Fumigation Chamber India, Fumigation Chamber Exporter, Fumigation, buy Fumigation Chamber, Fumigation Chamber, Analytical Research Equipment**

{ "@context": "http://schema.org/", "@type": "Product", "name": "Fumigation Chamber", "image": "https://www.jlabexport.com/images/catalog/product/1739525506fumigation-chamber.jpg", "description": "Low cost, fully equipped, all purpose laboratory ovens for sample drying, baking, annealing, conditioning, sterilizing, evaporating and dehydrating and other general laboratory work. Fully factory tested Sturdy construction of PCGI (Powder coated Galvanized Steel) Corrosion resistant galvanized steel interior OR of Stainless Steel. Primary hydraulic control thermostat sets desired oven temperature. Red pilot light indicates heater operation. Heat is transferred from the bottom up through the oven chamber by natural convection and exits through vent in the oven sides. Synthetic door gasket made of neoprene on the double walled door. User oriented design of shelves makes you adjust each space of shelves without difficulty. Heating elements are placed at bottom. Space between inner chamber and outer wall is filled with high grade mineral wool for minimal heat dissipation. Door fitted with heavy duty hinges and door handle ensuring there are no leakages through the door gasket. To work on 220/230V AV, 50/60 Hz supply. Fumigation Chamber Manufacturer, Fumigation Chamber Suppliers, Fumigation Chamber India, Fumigation Chamber Exporter, Fumigation, buy Fumigation Chamber, Fumigation Chamber, Analytical Research Equipment", "brand": "JLab Export", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "55", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "5" } }

---