



Product Code . JL-EGC-3895

Environmental Chamber

Description

Environmental Chamber Cooled Stability Chamber

Suitable for carrying out different quality control tests under controlled conditions of temperature and humidity.

The excellent quality of magnetic gum packing for the external door.

User oriented design of shelves makes you adjust each space of shelves without difficulty.

Inner chamber is made of stainless steel (S.S. 304 Grade) and outer wall of mild steel sheet duly painted and mounted on castor wheel.

High grade Polyurethane Foam (PUF) insulation between outer and inner chamber for minimal thermal loss.

Front double walled door is provided with lock and key arrangement.

A self-cooled air circulation fan is fitted to maintain uniform temperature and humidity conditions throughout the chamber.

Humidity is created through steam generation tank at base /top.

Provided with refrigeration system to control temperature range from 10°C to 60°C $\pm 1^\circ\text{C}$ and humidity (5% above ambient) from 40% to 95% RH $\pm 3\%$ RH at Cool Temperature.

Environmental Chamber Manufacturer, Environmental Chamber Suppliers, Environmental Chamber India, Environmental Chamber Exporter, Environmental Growth Chamber, buy

Environmental Chamber, Environmental Chamber, Analytical Research Equipment

```
{ "@context": "http://schema.org/", "@type": "Product", "name": "Environmental Chamber", "image":  
"https://www.jlabexport.com/images/catalog/product/1672515192environmental-chamber.jpg",  
"description": "Environmental Chamber Cooled Stability Chamber Suitable for carrying out different  
quality control tests under controlled conditions of temperature and humidity. The excellent quality of  
magnetic gum packing for the external door. User oriented design of shelves makes you adjust each  
space of shelves without difficulty. Inner chamber is made of stainless steel (S.S. 304 Grade) and  
outer wall of mild steel sheet duly painted and mounted on castor wheel. High grade Polyurethane  
Foam (PUF) insulation between outer and inner chamber for minimal thermal loss. Front double  
walled door is provided with lock and key arrangement. A self-cooled air circulation fan is fitted to  
maintain uniform temperature and humidity conditions throughout the chamber. Humidity is created  
through steam generation tank at base /top. Provided with refrigeration system to control temperature  
range from 10°C to 60°C ±1°C and humidity (5% above ambient) from 40% to 95% RH ±3% RH at  
Cool Temperature. Environmental Chamber Manufacturer, Environmental Chamber Suppliers,  
Environmental Chamber India, Environmental Chamber Exporter, Environmental Growth Chamber,  
buy Environmental Chamber, Environmental Chamber, Analytical Research Equipment", "brand":  
"JLab Export", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "55", "aggregateRating": {  
"@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount":  
"5" } }
```
