



**Product Code . JL-O-6346**

## Drying Cabinet/Oven

### Description

---

#### Drying Cabinet/Oven

This unit has double walled chamber with interior made of Stainless Steel and Exterior is either made of Mild Steel finished.

#### Standard Fitting:-

S.S Enclosure, Motor, Controller PID, Power Cord, Tube Heater, Rubber Gasket, S.S Tray, Door Lock.

#### Features:-

Designed, fabricated to suit various applications in Laboratory/Hospitals.

Double walled chamber with interior made of Stainless Steel and Exterior is either made of Stainless Steel/Mild Steel powder coated.

Gap of inner & outer walled filled with sufficiently thick Glass wool insulation.

Long lasting S.S. tubular heater are mounted at bottom to give uniform heating.

Motorized blower for maintaining uniform temp. with in chamber, blowing in Air from bottom.

Microprocessor based Controller cum Indicator with pt. 100 sensor.

Optional – P.I.D. Controller with Printer Interface P.I.D. Controller with PC Interface.

---

**Drying Cabinet Manufacturer, Drying Cabinet Suppliers, Drying Cabinet India, Drying Cabinet Exporter, Ovens, buy Drying Cabinet, Drying Cabinet, Analytical Research Equipment**

**Sizes:-**

Inner Size (Inch)	Capacity
300 x 300 x 300	30 Ltrs Approx
400 x 400 x 400	65 Ltrs Approx
500 x 500x 500	125 Ltrs Approx
600 x 600 x 600	220 Ltrs Approx
600 x 600 x 900	325 Ltrs Approx
2100 x 2100 x 1500	600 Ltrs Approx

{ "@context": "http://schema.org/", "@type": "Product", "name": "Drying Cabinet/Oven", "image": "https://www.jlabexport.com/images/catalog/product/1210427928drying-cabinet-oven.jpg", "description": "This unit has double walled chamber with interior made of Stainless Steel and Exterior is either made of Mild Steel finished. Standard Fitting:- S.S Enclosure, Motor, Controller PID, Power Cord, Tube Heater, Rubber Gasket, S.S Tray, Door Lock. Features:- Designed, fabricated to suit various applications in Laboratory/Hospitals. Double walled chamber with interior made of Stainless Steel and Exterior is either made of Stainless Steel/Mild Steel powder coated. Gap of inner & outer walled filled with sufficiently thick Glass wool insulation. Long lasting S.S. tubular heater are mounted at bottom to give uniform heating. Motorized blower for maintaining uniform temp. with in chamber, blowing in Air from bottom. Microprocessor based Controller cum Indicator with pt. 100 sensor. Optional – P.I.D. Controller with Printer Interface P.I.D. Controller with PC Interface. Drying Cabinet Manufacturer, Drying Cabinet Suppliers, Drying Cabinet India, Drying Cabinet Exporter, Ovens, buy Drying Cabinet, Drying Cabinet, Analytical Research Equipment", "brand": "JLab Export", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "55", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "5" } }

---