



**Product Code . JL-I-6363**

## **BOD Incubator**

### **Description**

---

#### **BOD Incubator**

They are most versatile for Biochemical Oxygen Demand determinations.

Castor wheel mounted cabinet is double walled with inner chamber of aluminum or S.S. and outer wall made up of M.S. Sheet duly powder coated.

The unit is provided with optimum thermal glass wool insulation.

Triple walled back of unit is fitted with two air circulation fans for maintaining temperature uniformly throughout the chamber.

Full view inner Perspex door permits inspection of specimens, without disturbing the chamber temperature.

Lock and Key arrangement is provided in the double walled outer door.

Unit is also fitted with door operated illumination lamp inside the chamber.

Refrigeration unit is formed by ISI marked compressor/cooling kit.

The front panel contains separate indicator lamps for main, O O heating and incoming voltage and supplied, which is completed with 3 shelves, temperature from 2 C to 60 C is controlled digitally, with an accuracy of 0.5 C.

Available standard capacity 6,10,12,15 Cu Ft respectively.

---

**BOD Incubator Manufacturer, BOD Incubator Suppliers, BOD Incubator India, BOD Incubator Exporter, buy BOD Incubator, Incubators, BOD Incubator, Analytical Research Equipments, buy BOD Incubator Online India**

{ "@context": "http://schema.org/", "@type": "Product", "name": "BOD Incubator", "image": "https://www.jlabexport.com/images/catalog/product/553962563bod-incubator.jpg", "description": "They are most versatile for Biochemical Oxygen Demand determinations. Castor wheel mounted cabinet is double walled with inner chamber of aluminum or S.S. and outer wall made up of M.S. Sheet duly powder coated. The unit is provided with optimum thermal glass wool insulation. Triple walled back of unit is fitted with two air circulation fans for maintaining temperature uniformly throughout the chamber. Full view inner Perspex door permits inspection of specimens, without disturbing the chamber temperature. Lock and Key arrangement is provided in the double walled outer door. Unit is also fitted with door operated illumination lamp inside the chamber. Refrigeration unit is formed by ISI marked compressor/cooling kit. The front panel contains separate indicator lamps for main, O O heating and incoming voltage and supplied, which is completed with 3 shelves, temperature from 2 C to 60 C is controlled digitally, with an accuracy of 0.5 C. Available standard capacity 6,10,12,15 Cu Ft respectively. BOD Incubator Manufacturer, BOD Incubator Suppliers, BOD Incubator India, BOD Incubator Exporter, buy BOD Incubator, Incubators, BOD Incubator, Analytical Research Equipments, buy BOD Incubator Online India", "brand": "JLab Export", "sku": "5", "gtin8": "5", "gtin13": "5", "gtin14": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "5" } }

---