



Product Code . JL-TWL-6657

RTD Studies in CSTR JLab

Description

RTD Studies in CSTR

- RTD Studies In CSTR Real reactors do not satisfy the idealized flow patterns, back mix flow or plug flow deviation from ideality can be due to channeling of fluid through the vessel, recycling of fluid within the vessel or due to the presence of stagnant region or pockets of fluid in the vessel.
- To predict the exact behavior of a vessel as a Chemicals reactor, RTD of stimulus response technique is used.
- The setup consists of one feed tank through which water is fed to the reactor.
- The flow rate can be adjusted by operating the needle valve and measured by Rota meter.
- The magnetic drive pump is used for circulation of feed.
- The continuously stirred tank reactor made of Stainless Steel is provided for understanding the R.T.D. characteristics.
- A syringe is used for dozing the tracer in the C.S.T.R Experiments To plot RTD curve for a CSTR Using pulse tracer To determine the Dispersion No Utilities Required Water Supply & Drain Electricity Supply: 1 Phase, 220 V AC, 0.5 kW Instruments, Laboratory Glassware and Chemicals required for analysis as per the system adopted.
- Chemical Reaction Engineering lab equipment manufacturers, exporters and Chemical Reaction Engineering Lab suppliers.

Contact JLab Export for your Educational School Science Lab Equipments. We are best burette pinchclip medium wall supplier, chemistry lab equipments manufacturers, chemistry lab equipments manufacturer, education lab supplies, educational biology lab equipments, educational biology lab instruments.
