

Product Code . JL-TWL-9119

Reverse Osmosis Ultra filtration Unit



Description

Reverse Osmosis Ultrafiltration Unit

Description:-

Comprehensive instrumentation is provided with digital meters displaying temperatures and system pressure.

This is fully self-contained in a mobile cabinet.

In addition to the membrane module, the cabinet also houses feed and permeate tanks, a plate heat exchanger and positive displacement pumps.

Connection to cooling water and a suitable electrical supply is all that is required for normal operation.

All parts in contact with the process fluid are constructed from hygienic design materials such as stainless steel, PTFE and silicone rubber.

The RO/UF unit has an efficient clean-in-place facility and is easily dismantled for servicing or maintenance.

It uses a membrane module which accommodates all PCI membrane types.

The unit is supplied with a pack of both R.O. membranes and U.F. membranes.

Membranes can be installed or removed rapidly for use in either process.

The filtration membranes differ only in length and quantity from those installed in the full-scale plant.

Using small quantities of process fluid, operating parameters can be established and then optimized to effect a confident transition to full-scale.

Specification:-

Flowrates: 30, 18, 15 and 9l/m

Pressures: Variable up to 55 bar

Diameter: 1.25cm

Area: 0.024m²

Tube-side Volume: 75ml

Typical Permeate Flow: 5-50ml/min

Feed Tank Capacity: 15 litres

Permeate Tank Capacity: 15 litres

Contact JLab Export for your Educational School Science Lab Equipments. We are best school science lab equipment suppliers in India, school science lab equipments exporter, school science lab equipments manufacturers, school science lab equipments manufacturer, school science lab equipments supplier, school science lab equipments suppliers.
